


## MPC3E



Software release	<ul style="list-style-type: none"> <li>MX240, MX480, and MX960 routers : Junos OS Release 12.1 and later</li> <li>MX2010 and MX2020 router: Junos OS Release 12.3 and later</li> </ul> <p>For information on which MICs are supported on this MPC, "<a href="#">MIC/MPC Compatibility</a>" on page 26.</p>
Description	<ul style="list-style-type: none"> <li>Power requirement: 10.83 A @ 48 V (440 W; plus 40 W for each of the two MICs)</li> <li>Requires high-capacity fan trays</li> <li>Weight: 14.94 lb (6.78 kg)</li> <li>Model number: MX-MPC3E-3D</li> <li>Name in the CLI: <b>MPCE Type 3 3D</b></li> </ul>
Hardware features	<ul style="list-style-type: none"> <li>Two slots for MICs</li> <li>Chipset for increased scaling for bandwidth, subscribers, and services</li> <li>Supports maximum transmission unit (MTU) size of 9,192 bytes for host bound packets. For Junos OS 16.1R1 and later releases, the MTU size supported is 9,500 bytes.</li> </ul>
Software features	<ul style="list-style-type: none"> <li>See "<a href="#">Protocols and Applications Supported by the MPC3E on MX Series Routers</a>" on page 343 for information about the protocols and applications that this MPC supports.</li> </ul>